










FLEXIBLE																		
	R1 - R1T DENUDE	R1T SANS DENUDAGE	R2 - R2T DENUDE	R2T SANS DENUDAGE	R3T	R6 B.P.	R7T/R8 THERMO	R9R (4SP)	4 SH									
3/16	JS 104	15,2	JS 12T04	16	JS 204	17,6	JS 12T04	16,7			JS 804	11,8						
	18				18													
1/4	JS 106	17,2	JS 12T06	18	JS 206	17,8	JS 12T06	19	JS 206	19	JS 606	14,8	JS 806	14,1	JS 906	19,2		
	21				21				21						21			
5/16	JS 108	18,8	JS 12T08	18,6	JS 208	20,3	JS 12T08	19,6			JS 608	17,2	JS 808	16,2				
	22				22													
3/8	JS 110	21	JS 12T10	20,5	JS 210	23	JS 12T10	21,3	JS 210	24	JS 610	18,9	JS 810	18,2	JS 910	23,2		
	23				23				23						23			
1/2	JS 113	25,4	JS 12T13	23,4	JS 213	25,7	JS 12T13	24,4	JS 213	26,8	JS 613	23,2	JS 813	22,2	JS 913	26,3		
	25				25				25						27			
5/8	JS 116	28,2	JS 12T16	27	JS 216	29,9	JS 12T16	28,2	JS 216	30,7	JS 616	25,8	JS 816	25,6	JS 916	30,2		
	28				28				28						31			
3/4	JS 119	32,2	JS 12T19	30,8	JS 219	33,5	JS 12T19	32	JS 219	34,8	JS 619	29,9	JS 819	29	JS 919	34,6		
	34				34				34						36			
1"	JS 125	39,8	JS 12T25	39,1	JS 225	41,2	JS 12T25	40,3	JS 225	42,1	JS 625	37,6	JS 825	36,8	JS 925	42,2		
	37				37				37						48			
1" 1/4	JS 132	46,6	JS 12T32	48,5	JS 232	50,8	JS 12T32	51							JS 932	54,6	JS 4SH32	48
	43				43										54		54	
1" 1/2	JS 138	53	JS 12T38	57	JS 238	56,7	JS 12T38	59,8							JS 938	59,2	JS 4SH38	58
	47				47										62		62	
2"	JS 150	66,2	JS 12T50	69,4	JS 250	69,5	JS 12T50	72,4							JS 950	74,6	JS 4SH50	70,5
	62				64										64		64	



 Longueur dénudage extérieur


 Diamètre de sertissage


 Jupe à utiliser

TABLEAU DE SERTISSAGE RACCORDS CMD (INTERLOCK)

(Version 1 - 09/08/13)

	 FLEX 4 SH		 FLEX 100R15	
3/4"	52	33,9		
	15		JMD19 4SH/R15 VOSS	
1"	67	41,5	67	41,5
	17		JMD25 4SH/R15 VOSS	
1"1/4	74	50,2	74	54,6
	21,5		JMD32 4SH VOSS	
1"1/2	81	58	81	61,3
	22		JMD38 4SH VOSS	
2"	85	74,2		
	29		JMD50 4SH VOSS	

 Longueur dénudage extérieur (mm)

 Longueur dénudage intérieur (mm)

 Diamètre sertissage

 Référence de la jupe

TABLEAU DE SERTISSAGE (version 1 - 06/08/2013)



FLEXIBLE	Flex Aspiration 811			Flex Compact 471TC			Flex R15 797TC		
	Série Embout	Longueur Insertion	∅ Sertissage	Série Embout	Longueur Insertion	∅ Sertissage	Série Embout	Longueur Insertion	∅ Sertissage
1/4				48	22	16,6			
5/16				48	24	18,3			
3/8				48	22	20,6			
1/2				48	24	23,6	77	35	23,9
5/8				48	25	26,9	77	39	27,1
3/4	48	25	32,7	48	25	30,7	77	45	31,9
1"	48	30	40,3	48	30	38,3	77	54	39,4
1" 1/4	48	46	51,3	48	46	50,3	77	64	50,3
1" 1/2	48	37	59,4	48	37	58,4			
2"	48	47	70,7	48	47	69,7			

Tolérance : +/- 0,25 mm